



REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	BROKEN	2020.04.28
B	MODIFY	BROKEN	2022.05.21
C	MODIFY	BROKEN	2022.12.03

RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ±0.05

- SPECIFICATIONS:
1. ELECTRICAL CHARACTERISTICS
 - 1-1. CONTACT RESISTANCE: 90 milliohms MAX.
 - 1-2. INSULATION RESISTANCE: 1,000 Megohms MIN.
 - 1-3. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC
- FOR 1 MINUTE.
2. SALT SPRAY: 48H.
 3. ROHS 2002/95/EC COMPLIANT.
 4. PACKING NUMBER : 1400 PCS/REEL.

TABLE:

P/N	PLATING
1040202AR001	1u"
1040202BR001	3u"

B	CONTACT	2	SUS301	Gold (SEE TABLE) plated on contact area All over Nickel Plated.
A	HOUSING	1	LCP E130I	CREAMY WHITE
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
DECIMALS:	ANGLES:			
X : ±0.5	X : ±2'			
X.X : ±0.3	X.X : ±1'			
X.XX : ±0.2				
TITLE:		2PIN SPRING BATTERY插板4.5H		
PART NO.	1040202XR001			
DWG	BROKEN			
CHKD	2022.12.03			
APVD				
SCALE 1:1	UNIT: mm			
CUSTOMER COPY	SIZE: A4	SHEET: 10F1	REV: C	

