





THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TETULL PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TETULL LTD.

ROHS Compliant



RECOMMENDED P.C.B. LAYOUT  
(General tolerance ±0.05)

- SPECIFICATIONS:
1. Current Rating: 0.5A AC/DC
  2. Contact Resistance: 40mΩ max
  3. Insulation Resistance: 1000MΩ min
  4. Withstanding Voltage: 500VAC/minute
  5. TEMPERATURE RANGE -40°C ~ +85°C

P/N	NOTES	DIM.A	DIM.B
1085001AR001	CF CARD 50P 板上臂长26.9	1.35	0.70
1085001AR002	CF CARD 50P 板下臂长26.9	0.70	1.35

C	FIXING	2	COPPER ALLOY 0.30t	Tin plated on Solder tail All over Nickel Plated
B	CONTACT	50	COPPER ALLOY 0.40t	Sold Finish on Contact Area Molte-Tin plated on Solder tail All over Nickel Plated
A	HOUSING	1	THERMOPLASTIC UL94-10	WHITE
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
DECIMALS:		ANGLES:		
X	±0.5	X	±2°	
X.X	±0.3	X.X	±1°	
X.XX	±0.2			
TITLE: CF CARD 50P 臂长26.9				
PART NO.		1085001AR00X		
DWG		TOM		
CHKD		2012.02.23		
APVD				
SCALE 1:1		UNIT: mm		
CUSTOMER COPY		SIZE: A4		
		SHEET: 10F1		
		REV: A		

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	TOM	2012.03.23