




THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TETULL PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TETULL LTD.

ROHS Compliant



2022 4 21
文控中心



RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ±0.05

DIMENSION INFORMATION	
DIM.A	P/N
2.65	1050622AR002
2.40	1050622AR003

C	SHELL	1	STAINLESS STEEL 0.15t	NI PLATING
B	CONTACT	6	COPPER ALLOY 0.15t	Gold plated on contact area Gold plated on Solder toll All over Nickel Plated
A	HOUSING	1	HIGH-TEMPERATURE PLASTIC UL94-V0	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
DECIMALS:		ANGLES:		
X	±0.5	X	±2°	
X.X	±0.3	X.X	±1°	
X.XX	±0.2			

SIM pin Assignment	
PIN#	Name
C1	VCC
C2	RST
C3	CLK
C4	RESERVED
C5	GND
C6	VPP
C7	I/O
C8	RESERVED

- NOTE:
- ELECTRICAL CHARACTERISTICS
 - 1-1. VOLTAGE RATING: 10V DC.
 - 1-2. CURRENT RATING: 0.5 A.
 - 1-3. CONTACT RESISTANCE: 50 milliohms MAX.
 - 1-4. INSULATION RESISTANCE: 1000 Megohms MIN.
 - 1-5. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
 2. MECHANICAL CHARACTERISTICS
 - 2-1. RETENTION FORCE: 100gf MIN./PIN.
 - 2-2. DURABILITY: 5000 CYCLES.
 3. SALT SPRAY: 24H.
 4. OPERATING TEMPERATURE: -40C~85C.
 5. RoHS 2002/95/EC COMPLIANT.
 6. MPQ : 1000PCS/REEL.



TITLE:	
MICRO SIM CARD 6P W/LOCATION	
PART NO.	1050622AR002&003
DWN	BROKEN
CHKD	2018.08.30
APVD	
SCALE 1:1	UNIT: mm
CUSTOMER COPY	SIZE: A4
	SHEET: 10F1
	REV: C

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	TOM	2011.03.22
B	MODIFY	BROKEN	2015.06.17
C	MODIFY	BROKEN	2018.08.30