

ROHS Compliant

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TETULL PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TETULL LTD.

NOTE: SIM CARD INSERTION DIRECTION

1. ELECTRICAL CHARACTERISTICS
- 1-1. VOLTAGE RATING: 15V DC.
- 1-2. CURRENT RATING: 1.0 A.
- 1-3. CONTACT RESISTANCE: 50 milliohms MAX.
- 1-4. INSULATION RESISTANCE: 1000 Megohms MIN.
- 1-5. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
2. MECHANICAL CHARACTERISTICS
- 2-1. RETENTION FORCE: 100gf MIN./PIN.
- 2-2. DURABILITY: 5000 CYCLES.
3. SALT SPRAY: 24H.
4. OPERATING TEMPERATURE: -40°C~85°C.
5. ROHS 2002/95/EC COMPLIANT.
6. MPQ : 1500PCS/REEL.

RECOMMENDED PCB LAYOUT  
GENERAL TOLERANCE ±0.05

DIMENSION INFORMATION

P/N	DIM.A	PLATING
1050605DR001	1.80	1u"
1050605DR002	2.00	1u"
1050605DR010	1.80	10u"

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	TOM	2011.03.22
B	MODIFY	BROKEN	2013.01.16

NO	DESCRIPTION	QTY	MATERIAL	TITLE: SIM CARD 6P SIMPLE TYPE (10.07.80)
B	CONTACT	6	C5210 0.15t	Gold plated on contact area Gold plated on Solder tail All over Nickel plated
A	HOUSING	1	LCP	BLACK

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS:	ANGLES:
X : ±0.5	X : ±2°
X.X : ±0.3	X.X : ±1°
X.XX : ±0.2	

CUSTOMER COPY

PART NO.	DWG	CHKD	APVD	SCALE	UNIT	SHEET	REV.
1050605DR00XX	BROKEN			A4	mm	10F1	B

TETULL CORPORATION