



THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TETULL PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TETULL LTD.




NOTE:

- 1. ELECTRICAL CHARACTERISTICS
 - 1-1. VOLTAGE RATING: 15V DC.
 - 1-2. CURRENT RATING: 1.0 A.
 - 1-3. CONTACT RESISTANCE: 50 milliohms MAX.
 - 1-4. INSULATION RESISTANCE: 1000 Megohms MIN.
 - 1-5. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
- 2. MECHANICAL CHARACTERISTICS
 - 2-1. CONTACT NORMAL FORCE: 0.3~0.9N CONTACT.
 - 2-2. DURABILITY: 5000 CYCLES.
 - 3. SALT SPRAY: 24H.
 - 4. OPERATING TEMPERATURE: -40°C~85°C.
 - 5. RoHS 2002/95/EC COMPLIANT.
 - 6. MPO : 750PCS/REEL.

RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ±0.05

SIM pin Assignment		
PIN#	PAD#	Nome
P1	C1	VCC
P2	C2	RST
P3	C3	CLK
P5	C5	GND
P6	C6	VPP
P7	C7	I/O



REFERENCE SIM CARD PLUG

TABLE:

ITEM	P/N	NOTE
1	1050601AR003	W/POST
2	1050601AR013	W/O POST

F	SHELL	1	STAINLESS STEEL 0.15T	Ni/Au PLATING
E	SPRING	1	SMP	-----
D	LINK	1	STAINLESS STEEL	-----
C	SLIDER	1	HIGH-TEMPERATURE PLASTIC UL94-V0	BLACK
B	CONTACT	6	COPPER ALLOY 0.15t	Gold plated on contact area Gold Flash on Solder tail All over Nickel Plated .
A	HOUSING	1	HIGH-TEMPERATURE PLASTIC UL94-V0	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
DECIMALS:	ANGLES:			
X :±0.5	X :±2°			
X.X :±0.3	X.X :±1°			
X.XX :±0.2				



CUSTOMER COPY SIZE: A4 SHEET: 10F1 REV: C