

ROHS Compliant

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TETULL PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TETULL LTD.

SECTION E

Recommend PCB LAYOUT  
(TOLERANCE:±0.05)

NOTE:

1. ELECTRICAL CHARACTERISTICS
  - 1-1. VOLTAGE RATING: 10V DC.
  - 1-2. CURRENT RATING: 0.5 A.
  - 1-3. CONTACT RESISTANCE: 80 milliohms MAX.
  - 1-4. INSULATION RESISTANCE: 1000 Megohms MIN.
  - 1-5. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
2. MECHANICAL CHARACTERISTICS
  - 2-1. RETENTION FORCE: 100gf MIN./PIN.
  - 2-2. DURABILITY:5000 CYCLES.
3. SALT SPRAY: 24H.
4. OPERATING TEMPERATURE:-40°C~85°C.
5. ROHS 2002/95/EC COMPLIANT.
6. MPQ : 100PCS/TRAY.

REV.	ECN NO.	OR DESCRIPTION	REVISED	DATE
A		PRODUCT RELEASE	ARES	2018.5.14
B		MODIFY	BROKEN	2020.8.20

B	CONTACT	8	COPPER ALLOY	Gold plated on contact area Tin plated on Solder tail All over Nickel Plated.
A	HOUSING	1	HIGH-TEMPERATURE PLASTIC	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
DECIMALS:	ANGLES:			
X : ±0.5	X : ±2°			
X.X : ±0.3	X.X : ±1°			
X.XX : ±0.2				
TITLE: TF CARD 8P DIP 簡易				
PART NO.		1060804T001		
DWN		BROKEN		
CHKD		2020.8.20		
APVD				
SCALE 1:1		UNIT: mm		
SIZE: A4		SHEET: 10F1		
CUSTOMER COPY		REV: B		

TETULL CORPORATION