

ROHS Compliant

Pin No.	Pin assignment
1	DAT2
2	CD/DAT3
3	CMD
4	VDD
5	CLK
6	VSS
7	DAT0
8	DAT1

NOTE:

- ELECTRICAL CHARACTERISTICS
 - VOLTAGE RATING: 10V DC.
 - CURRENT RATING: 0.5 A.
 - CONTACT RESISTANCE: 80 milliohms MAX.
 - INSULATION RESISTANCE: 1000 Megohms MIN.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
- MECHANICAL CHARACTERISTICS
 - RETENTION FORCE: 100gf MIN./PIN.
 - DURIBILITY: 5000 CYCLES.
 - SALT SPRAY: 24H.
 - OPERATING TEMPERATURE: -40°C~85°C.
 - ROHS 2002/95/EC COMPLIANT.

TABLE:

P/NO.	PACKING
1060803PT002	50PCS/BAG
1060803AR006	1800PCS/REEL

B	CONTACT	8	COPPER ALLOY 0.15t	Tin plated on Solder tail All over Nickel Plated.
A	HOUSING	1	HIGH-TEMPERATURE PLASTIC UL94-V0	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS:	ANGLES:
X : ±0.5	X : ±2°
X.X : ±0.3	X.X : ±1°
X.XX : ±0.2	

TITLE: T-FLASH CONN SIMPLE SOCKET
 PART NO. 1060803PT002&AR006
 DWG BROEKNV 2010.04.21
 CHKD
 APVD
 SCALE 1:1
 UNIT: mm
 SHEET: 10F1
 REV: B

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	JAMES	2008.03.29
B	MODIFY	BROKEN	2010.04.21

TETULL CORPORATION