




REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	BROKEN	2015.12.08
B	MODIFY	ZHARKO	2023.11.07

ROHS Compliant


THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TETULL PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TETULL LTD.




CARD FIXED DIMENSION REFERENCE

NOTE:

1. ELECTRICAL CHARACTERISTICS
  - 1-1. VOLTAGE RATING: 10V DC.
  - 1-2. CURRENT RATING: 0.5 A.
  - 1-3. CONTACT RESISTANCE: 80 milliohms MAX.
  - 1-4. INSULATION RESISTANCE: 1000 Megohms MIN.
  - 1-5. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
2. MECHANICAL CHARACTERISTICS
  - 2-1. CONTACT NORMAL FORCE: 0.3~0.9N CONTACT.
  - 2-2. DURIBILITY: 5000 CYCLES.
  3. SALT SPRAY: 24H.
  4. OPERATING TEMPERATURE: -40°C~85°C.
  5. RoHS 2011/65/EU COMPLIANT.
  6. MPQ : 1500PCS/RELL.



Pin No.	Pin assignement	Pin No.	Pin assignement
1	DATA2	6	VSS
2	CD/DAT3	7	DAT0
3	CMD	8	DAT1
4	VDD	Cd	
5	CLK	G	



C	SHELL
B	CONTACT
A	HOUSING
NO	DESCRIPTION
QTY	MATERIAL
UNLESS OTHERWISE SPECIFIED TOLERANCES	
DECIMALS:	ANGLES:
X : ±0.5	X : ±2°
XX : ±0.3	XX : ±1°
XXX : ±0.2	

C	SUS 201	Ni PLATING
B	C2680	Gold Flash On Contact Area Tin plated on Solder toll All over Nickel Plated .
A	LCP	BLACK
QTY	MATERIAL	PLATING & COLOR
TITLE: T-FLASH CONN HING TYP 1.5H		
PART NO.	1060801GR205	
DWG	ZHARKO	2023.11.07
CHKD		
APVD		
SCALE 1:1	UNIT: mm	
CUSTOMER COPY	SIZE: A4	SHEET: 10F1
		REV: B

