

ROHS Compliant

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TETULL PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TETULL LTD.

TABLE:

P/N.	TYPE
1030515AR001	有柱
1030515AR005	无柱

PIN	PIN NAME
1	VBUS
2	D-
3	D+
4	ID
5	GND

NO	DESCRIPTION	QTY	MATERIAL
C	SHELL	1	C2680
B	CONTACT	5	C2680
A	HOUSING	1	LCP

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS: ANGLES:

X.XX ±0.2 X.X ±1°

X.XX ±0.3 X.X ±1°

X.XX ±0.5 X ±2°

TITLE: MTC80 USB SP B TYPE SIMT 四脚插板卷边

PART NO. 1030515AR00X

DWG BROKEN 2018.07.03

CHKD

APVD

SCALE 1:1 UNIT: mm

SIZE: A4 SHEET: 10F1 REV: B

REV/ECN NO OR DESCRIPTION	REVISED	DATE
A PRODUCT RELEASE	JAMES	2014.04.11
B MODIFY	BROKEN	2018.07.03

NOTE:

- ELECTRICAL CHARACTERISTICS
 - 1-1. VOLTAGE RATING: 30V AC
 - 1-2. CURRENT RATING: 2.0A (pin1,5); 0.5A (pin2,3,4)
 - 1-3. CONTACT RESISTANCE: 50 milliohms MAX.
 - 1-4. INSULATION RESISTANCE: 100 Megohms MIN.
 - 1-5. DIELECTRIC WITHSTANDING VOLTAGE: 250V AC FOR 1 MINUTE.
- MECHANICAL CHARACTERISTICS
 - 2-1. MATING&UMMATING FORCE: 0.8kgf~3.5kgf
 - 2-2. DURIBILITY: 5000CYCLES
 - 3. SALT SPRAY: 24H
 - 4. OPERATING TEMPERATURE: -40°C~85°C
 - 5. ROHS 2002/95/EC COMPLIANT.
 - 6. MPQ : 1500PCS/REEL.

TETULL CORPORATION