





THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TETULL PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TETULL LTD.



REV.	ECN NO	OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	MIKE	2019.10.09	
B	MODIFY	BECKEN	2020.05.13	

NOTE:

- ELECTRICAL CHARACTERISTICS
 - VOLTAGE RATING: 30V AC
 - CURRENT RATING: 2.0A
 - CONTACT RESISTANCE: 50 milliohms MAX.
 - INSULATION RESISTANCE: 100 Megohms MIN.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
- MECHANICAL CHARACTERISTICS
 - MATING&UNMATING FORCE: 0.7kgf~3.5kgf
 - DURIBILITY: 10000CYCLES
 - SALT SPRAY: 24H
 - OPERATING TEMPERATURE: -40C~85C
 - RoHS 2002/95/EC COMPLIANT.
 - CRITICAL DIMENSIONS : ∇

D	PCB	1	FR4-1	T-045
C	SHELL	1	SPCC 0.30t	NI
B	CONTACT	10	CS191 0.20t	Gold Flash On Contact Area Tin plated on Solder tail All over Nickel Plated.
A	HOUSING	1	LCP	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
DECIMALS:	ANGLES:			
X : ±0.5	X : ±2°			
X.X : ±0.3	X.X : ±1°			
X.XX : ±0.2				
  TITLE: MINI 10P公头绿PCB板壳L=17.0 (10点) 外壳脚固定 PART NO. 10310026R075 DWG BROKEN 2020.05.13 CHKD APVD SCALE 1:1 UNIT: mm 				

