



REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	TOM	2011.03.22


ROHS Compliant



- NOTE:
- ELECTRICAL CHARACTERISTICS
 - VOLTAGE RATING: 30V MAX
 - CURRENT RATING: 2.0A MAX
 - CONTACT RESISTANCE: 30 milliohms MAX.
 - INSULATION RESISTANCE: 1000 Megohms MIN.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
 - MECHANICAL CHARACTERISTICS
 - MATING FORCE: 35N MAX
 - UNMATING FORCE: 10N MIN
 - DURIBILITY: 5000 CYCLES
 - SALT SPRAY: 24H
 - OPERATING TEMPERATURE: -40C~85C
 - RoHS 2002/95/EC COMPLIANT.
 - MPQ : 100PCS/TRAY.



THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TETULL PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TETULL LTD.



C	SHELL	1	SPCC				
B	TERMINAL	4	COPPER ALLOY				
A	HOUSING	1	THERMOPLASTIC UL94-V0				
NO	DESCRIPTION	QTY	MATERIAL				
UNLESS OTHERWISE SPECIFIED TOLERANCES				TITLE: USB A/F 4P SMT			
DECIMALS:				PART NO.	1020401AT007&008		
ANGLES:				DWG	TOM		
X.XX				CHKD			
X.XX				APVD			
X.XX				SCALE 1:1	UNIT: mm		
X.XX				SIZE: A4	SHEET: 10F1		



CUSTOMER COPY